

SAMSON ULTL30



Special Features: 2 hour, 350°F factory fire rating.

Body & Door: Multi-layered structure that combines outer and inner steel plates enclosing a monolithic material. The door is reinforced with anti-penetration alloy grid, providing high protection against concentrated attacks with mechanical and electrical tools.

Bolts & Locking Mechanisms: Three-way active boltwork with Bolt detent mechanism, Double-action locking mechanism. Glass plate relocking protection on all locks.

Locks: Two UL approved locks. Mechanical or digital combination lock and a high security key lock.

Interior Fitting: Adjustable removable shelves. A hole for an alarm system connection - optional.

ISM

SINCE 1914

SAMSON ULTL30

U.L. APPROVED TL-30


against concentrated attacks with mechanical and electrical tools.
The same high quality construction as the highest rated safes at an affordable price.



Model	Inside Sizes			Outside Sizes			Volume	Weight*	Shelves
	H	W	D	H	W	D	CuFt	Lbs	
Samson 2524	25	24	20	29	28	28	6.9	1097	1
Samson 3524	35	24	20	39	28	28	9.7	1349	2
Samson 4524	45	24	20	49	28	28	12.5	1653	3
Samson 5524	55	24	20	59	28	28	15.3	2045	4
Samson 6528	65	28	20	69	32	28	21.1	2440	5
Samson 6034	60	34	20	69	38	28	23.6	2522	5
Samson 6536	65	36	26	69	40	34	35.2	2976	5
Samson 7236	72	36	26	76	40	72	39	3406	5

- * Weight Tolerance - 5%.
- ** Dimensions Tolerance - ±0.5".
- *** Add 2" to outside depth for 3-Spokes Operating Handle.
- **** Add 3.55" to outside depth for Pull-Handle.

Colors:



RAL 7016

Add Ons:

- Preparation (only) for movement time-lock - No charge - By Request
- Custome interior secured compartments - By Request
- Additional shelves - By Request
- Anchoring to the floor.

